

FAG B71901-C-T-P4S参数

| | | | | |
|--------|----------------------|--------|-------|-------------|
| 基本额定载荷 | C_{0r} | 1310 | N | 基本额定静载荷，径向 |
| 系数 | f_0 | 14.7 | | - |
| 极限转速 | $n_{G \text{ Fett}}$ | 67000 | r/min | 脂润滑时的极限转速 |
| | $n_{G \text{ Öl}}$ | 100000 | r/min | 最少油润滑时的极限转速 |
| 疲劳极限载荷 | C_{ur} | 135 | N | 疲劳极限载荷，径向 |
| 尺寸 | B | 6 | mm | - |
| | a | 5 | mm | - |
| | $D_a \text{ H12}$ | 21.5 | mm | - |
| | $d_a \text{ h12}$ | 15 | mm | - |
| | $r_{1 \text{ min}}$ | 0.3 | mm | - |
| | $r_{a \text{ max}}$ | 0.3 | mm | - |
| | $r_{al \text{ max}}$ | 0.3 | mm | - |
| | r_{min} | 0.3 | mm | - |
| 重量 | m | 11 | g | 质量 |
| 基本额定载荷 | C_r | 3400 | N | 基本额定动载荷，径向 |
| 尺寸 | d | 12 | mm | - |
| | D | 24 | mm | - |

FAG B71901-C-T-P4S图片



