

## NACHI 5220NR参数

|           |          |         |       |      |
|-----------|----------|---------|-------|------|
| 外形尺寸      | d        | 100     | mm    | 内径   |
|           | D        | 180     | mm    | 外径   |
|           | B        | 60.3    | mm    | 宽度   |
|           | r        | 2.1~4   | mm    | 轴向   |
|           | r        | 2.1~6.5 | mm    | 轴向   |
| 止动槽和止动环尺寸 | D1 (max) | 173.66  | mm    | (最大) |
|           | a (max)  | 5.69    | mm    | (最大) |
|           | b (max)  | 3.5     | mm    | (最大) |
|           | D2 (max) | 192.9   | mm    | (最大) |
|           | f (max)  | 3.1     | mm    | (最大) |
| 安装尺寸      | da (min) | 112     | mm    | (最小) |
|           | Da (max) | 168     | mm    | (最大) |
|           | ra (max) | 2       | mm    | (最大) |
|           | Dx (min) | 195     | mm    | (最小) |
|           | Cy (max) | 8.4     | mm    | (最大) |
| 重量        | Mass     | 5780    | g     | 重量   |
| 基本额定载荷    | Cr       | 168000  | N     | 动载荷  |
|           | Cor      | 159000  | N     | 静载荷  |
| 极限速度      | Grease   | 2400    | r/min | 脂润滑  |
|           | Oil      | 3200    | r/min | 油润滑  |

## NACHI 5220NR图片

参考资料:<http://www.sozhou.com/p/ffee7670.html>

